

FEATURES

- SAFETY SWITCH - INSTANT SHUT OFF
- In - Operation indicators
- **800v - 35000v in one instrument**
- Volume adjustment for use in loud environments
- Super Bright visual holiday indicator
- Ergonomic handle and grip
- Low battery voltage indicator
- Regulated voltage
- Push button operation
- Compatible with Models AP/S1 & AP/S2 accessories (wand, battery, ground cable)

Kit Includes:

Instrument
 (2) Batteries, w/ Case
 Ground Cable
 HV Cable
 Wand Handle
 Inspection Paddle
 Carrying Case
 Instruction Manual
 Letter of Calibration

Construction:

- Rugged design for long life
- Water & Dust Resistant Carrying Case
- Weather sealed
- Solid state electronics

Application

- Pipelines and other coated structures
- Wide variety of coatings materials
- Thin to thick coatings

Specifications

- Pulsating DC output voltage
- Low: 800v to 8,000v
- High: 3,500v to 35,000v
- 100v Resolution (Meter)
- +/- 5% Accuracy
- Battery operated (6v)
- 110v AC Charger (220v available)

Dimensions

- 2.5" x 21.5" x 2.75" Instrument only
- 5" x 2.5" x 5.5" Battery box

Carrying Case

- 40.5" x 17" x 7" (1028.7 x 431.8 x 177.8mm)
- 40lbs (18.14kg) Shipping Weight

